WEST Search History

| Hide Items | Restore | Clear | Cancel |

DATE: Wednesday, February 09, 2005

Hide?	Set Name	Query	Hit Count
		DB=USPT,EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=OR	
☐	L9	L8 same (power near2 (conserv$7 or consum$7))	6
☐	L8	l4 same card	58
☐	L7	L6 same power$4	12
☐	L6	(card adj bus adj controller)	89
☐	L5	L4 same ((board or card) near3 (inser$4 or remov$4))	15
☐	L4	((turn$4 adj off) or (shut$4 adj off) or (shut$4 adj down) or (power$4 near2 cutoff)) near2 (bridge or controller)	7177
☐	L3	((turn$4 adj off) or (shut$4 adj off) or (shut$4 adj down) or (power$4 near2 cutoff)) with (bridge or controller)	22365
☐	L2	((turn$4 adj off) or (shut$4 adj off) or (shut$4 adj down) or (power$4 near2 cutoff)) same (bridge or controller)	40571
☐	L1	6804300.pn.	4

END OF SEARCH HISTORY

☐ Generate Collection   Print

L5: Entry 2 of 15   File: USPT   Mar 16, 2004

DOCUMENT-IDENTIFIER: US 6708283 B1
** See image for Certificate of Correction **
TITLE: System and method for operating a system with redundant peripheral bus
controllers

Detailed Description Text (36):
The enable lines 65 and 63 connect also to the power controller 62. As the front
panel board 66 is removed, the power controller turns off and powers down the
board. The power ramps down, however, so that the switches 60 turn off before the
power is fully off. This ensures that the switches 60 operate properly to protect
the bus signal pins as the board is removed.

☐ �－Generate Collection－▏ ▏Print▏

L5: Entry 8 of 15   File: USPT   Sep 23, 1997

DOCUMENT-IDENTIFIER: US 5671368 A
TITLE: PC card controller circuit to detect exchange of PC cards while in suspend
mode

Detailed Description Text (20):
In addition to the normal operating mode and the lower power, suspend operating
mode of the PC Card controller 16, the computer 10 may be designed to permit a
computer program executed by the CPU 12 to turn-off electrical power that is
normally supplied to the PC Card controller 16. To prevent failing to detect an
exchange of PC Cards 24 while electrical power to the PC Card controller 16 is
turned-off, a power-on initialization sequence performed by the PC Card controller
16 every time the PC Card controller 16 is turned-on also causes the fake
interrupt-generator 86 to generate an interrupt faking insertion of a PC Card 24
into the PC Card socket 22 regardless of whether such an event has actually
occurred. In this way, even if electrical power is removed from the PC Card
controller 16, a PC Card controller 16 in accordance with the present invention
prevents the computer 10, upon restoring the PC Card controller 16 to normal
operation after being turned-off, from applying an improper voltage to a PC Card 24
that was exchanged for another, different voltage, PC Card 24 while the PC Card
controller 16 was turned-off, or from experiencing a software breakdown due to a
failure to detect an exchange of PC Cards while the PC Card controller 16 was
turned-off.

Hit List

Search Results - Record(s) 1 through 1 of 1 returned.

☐ 1. Document ID: JP 2001211402 A

L10: Entry 1 of 1   File: JPAB   Aug 3, 2001

PUB-NO: JP02001211402A
DOCUMENT-IDENTIFIER: JP 2001211402 A
TITLE: TELEVISION RECEIVER

PUBN-DATE: August 3, 2001

INVENTOR-INFORMATION:
NAME   COUNTRY

KONDO, TAKAHIRO
ASAO, MOTOAKI

ASSIGNEE-INFORMATION:
NAME   COUNTRY
SANYO ELECTRIC CO LTD

APPL-NO: JP2000015337
APPL-DATE: January 25, 2000

INT-CL (IPC): H04 N 5/63; G06 K 19/00; H04 N 7/167; H04 N 7/20

ABSTRACT:

PROBLEM TO BE SOLVED: To provide a television receiver that can reduce power consumption.

SOLUTION: The television receiver is provided with a switch that receives a digital reception circuit power supply even at power off of the receiver and turns on/off the supply of the digital reception circuit to a digital reception circuit, a means that discriminates whether or not a memory card is connected to a memory card connector at power off of the receiver, a means that turns on the switch when it is discriminated that the memory card is connected to the memory card connector, and a means that turns off the switch when it is discriminated that the memory card is not connected to the memory card connector.